



Ferrolì

RITA ONLINE SERIES
ELECTRIC INSTANT WATER HEATERS

RITA ONLINE SERIES


ELECTRIC INSTANT WATER HEATERS

Dimension: Height 7½" x Width 11" x Depth 4¼"




Ferrolì's little wonder, the 'RITA' series of Electric Instant Water Heaters incorporates the latest Online heating technology for quick and efficient delivery of hot water

Advanced Features



Online Heating Technology




Over Temperature Protection



Multiple Power Option



Flow Sensor Switch



Working LED Indicator



Multipoint Installation



Rust Proof
ABS Body

Product Specification :

Model	Capacity	Wattage (in kw)	Voltage	Dimension H x W x D (in mm)	Position of Knob			
					OFF	•	••	•••
RITA-FS4.5TM	Online Instant	4.5	230V/50Hz	186 x275 x107	OFF	2	2.5	4.5
RITA-FS5.7TM	Online Instant	5.7	230V/50Hz	186 x275 x107	OFF	2.2	3.5	5.7
RITA-FS 7.0TM	Online Instant	7.0	230V/50Hz	186 x275 x107	OFF	2.8	4.2	7.0
RITA-FS 7.5TM	Online Instant	7.5	230V/50Hz	186 x275 x107	OFF	3	4.5	7.5
RITA-FS9.5TM	Online Instant	9.5	230V/50Hz	186 x275 x107	OFF	4.5	5	9.5

Technical Specifications & Recommended Shower Heads



FERROLI ON LINE INSTANT WATER HEATER - TECHNICAL SPECIFICATIONS					
Models	RITA 4.5	RITA 5.7	RITA 7.0	RITA 7.5	RITA 9.5
Power- Optional (Kw)	2.0/2.5/4.5	2.5/3.2/5.7	2.8/4.2/7.0	3.0/4.5/7.5	4.5/5.0/9.5
Power- Max (Kw)	4.5	5.7	7.0	7.5	9.5
Voltage	220 ~ 240 V Ac	220 ~ 240 V Ac	220 ~ 240 V Ac	220 ~ 240 V Ac	220 ~ 240 V Ac
Phase	Single	Single	Single	Single	Single/2 Phase
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Wire Size	2.5 mm ²	4.0 mm ²	4.0 mm ²	6.0 mm ²	10.0 / 2.5 mm ²
Recommended Circuit Breaker	25 A	32 A	32 A	40 A	60 / 25 A
Min Water Flow Rate	2 litres/min	2 litres/min	2 litres/min	2 litres/min	2 litres/min
Min Water Pressure	0.8 Kg/cm ²	0.8 Kg/cm ²	0.8 Kg/cm ²	0.8 Kg/cm ²	0.8 Kg/cm ²
Max Water Pressure	6.0 Kg/cm ²	6.0 Kg/cm ²	6.0 Kg/cm ²	6.0 Kg/cm ²	6.0 Kg/cm ²
Water Connection (Dia)	15mm / ½" BSP	15mm / ½" BSP	15mm / ½" BSP	15mm / ½" BSP	15mm / ½" BSP
Recommended for Shower Head	upto 4"	upto 6"	upto 8"	upto 8"	10 to 12"
Dimensions (HxWxD) mm	186 x 275 x 107	186 x 275 x 107	186 x 275 x 107	186 x 275 x 107	186 x 275 x 107
Weight	1.5 Kg	1.5 Kg	1.5 Kg	1.5 Kg	1.5 Kg
MRP August 2021	₹ 7,140	₹ 7,745	₹ 9,380	₹ 9,380	₹ 12,090
Availability	Ex-stock	Ex-stock	Ex-stock	Ex-stock	Ex-stock

INSTALLATION GUIDELINES

For best performance install product closest to the point of usage.

Select a model with the right wattage depending on the shower head size/jet nozzle applications.

Ensure that the right wiring size has been provided.

Recommended inlet water pressure of not > 3.0 to 3.5 Bar for best results.

If inlet pressure exceeds 6 Bar, then a pressure reducing valve should be installed.

The water flow at outlet is always lower than that at the inlet, as hot water flow is set at max6 LPM.

Free basic installation service is provided against registration on 18001039533/What's Ap: 7349508533

Visit us at: www.ferrolis.co.in --- for details on all other available range of Ferrolis water heaters - 1 Ltr upto 500 Ltr.